

MATERIAL SAFETY DATA SHEET

1,2-DICHLOROETHANE 99% AR (Ethylene Chloride) MSDS CAS: 107-06-2

Section 1: Chemical Product and Company Identification

Section 1: Chemical Product

Product Name: 1,2-Dichloroethane AR

CAS#: 107-06-2

Synonym: Ethylene Dichloride

Chemical Name: 1,2-Dichloroethane AR

Chemical Formula: C₂H₄CL₂

Brand: OXFORD

Details Of The Supplier Of The Safety Data Sheet :

Company identification: **OXFORD LAB FINE CHEM LLP**
Unit. No. 12, 1st Floor, Neminath Industrial Estate No. 6,
Navghar, Vasai (East). Palghar - 401 210.
Mumbai, Maharashtra, INDIA.
Tel: 91-250-2390989
Tel/Fax: 91-250-2390032

Section 2: Composition and Information on Ingredients

Composition:

Name	CAS #	% by Weight
1,2-Dichloroethane AR	107-06-2	100

Toxicological Data on Ingredients: 1,2-Dichloroethane: ORAL (LD50): Acute: 670 mg/kg [Rat]. 413 mg/kg [Mouse]. DERMAL (LD50): Acute: 2800 mg/kg [Rabbit]. VAPOR (LC50): Acute: 1414.2 ppm 4 hour(s) [Rat].

Section 3: Hazards Identification

Potential Acute Health Effects:

Extremely hazardous in case of ingestion. Very hazardous in case of eye contact (irritant), of inhalation. Hazardous in case of skin contact (irritant). Corrosive to skin and eyes on contact. Liquid or spray mist may produce tissue damage particularly on mucous membranes of eyes, mouth and respiratory tract. Skin contact may produce burns. Inhalation of the spray mist may produce severe irritation of respiratory tract, characterized by coughing, choking, or shortness of breath. Inflammation of the eye is characterized by redness, watering, and itching.

Potential Chronic Health Effects:

Very hazardous in case of ingestion, of inhalation. **CARCINOGENIC EFFECTS:** Classified + (PROVEN) by OSHA. Classified 2B (Possible for human.) by IARC. Classified 2 (Reasonably anticipated.) by NTP. **MUTAGENIC EFFECTS:** Not available. **TERATOGENIC EFFECTS:** Not available. **DEVELOPMENTAL TOXICITY:** Not available. The substance is toxic to lungs, the nervous system, liver, mucous membranes. Repeated or prolonged exposure to the substance can produce target organs damage. Repeated or prolonged contact with spray mist may produce chronic eye irritation and severe skin irritation. Repeated or prolonged exposure to spray mist may produce respiratory tract irritation leading to frequent attacks of bronchial infection.

Section 4: First Aid Measures

Eye Contact:

Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open. Cold water may be used. Do not use an eye ointment. Seek medical attention.

Skin Contact:

If the chemical got onto the clothed portion of the body, remove the contaminated clothes as quickly as possible, protecting your own hands and body. Place the victim under a deluge shower. If the chemical got on the victim's exposed skin, such as the hands: Gently and thoroughly wash the contaminated skin with running water and non-abrasive soap. Be particularly careful to clean folds, crevices, creases and groin. If irritation persists, seek medical attention. Wash contaminated clothing before reusing.

Serious Skin Contact:

Wash with a disinfectant soap and cover the contaminated skin with an anti-bacterial cream. Seek immediate medical attention.

Inhalation:

Allow the victim to rest in a well ventilated area. Seek immediate medical attention.

Section 4: First Aid Measures (Continued)

Serious Inhalation:

Evacuate the victim to a safe area as soon as possible. Loosen tight clothing such as a collar, tie, belt or waistband. If breathing is difficult, administer oxygen. If the victim is not breathing, perform mouth-to-mouth resuscitation. **WARNING:** It may be hazardous to the person providing aid to give mouth-to-mouth resuscitation when the inhaled material is toxic, infectious or corrosive. Seek immediate medical attention.

Ingestion:

Do not induce vomiting. Examine the lips and mouth to ascertain whether the tissues are damaged, a possible indication that the toxic material was ingested; the absence of such signs, however, is not conclusive. Loosen tight clothing such as a collar, tie, belt or waistband. If the victim is not breathing, perform mouth-to-mouth resuscitation. Seek immediate medical attention.

Serious Ingestion: Not available.

Section 5: Fire and Explosion Data

Flammability of the Product: Flammable.

Auto-Ignition Temperature: 413°C (775.4°F)

Flash Points: CLOSED CUP: 13°C (55.4°F). OPEN CUP: 18°C (64.4°F).

Flammable Limits: LOWER: 6.2% UPPER: 15.6%

Products of Combustion: These products are carbon oxides (CO, CO₂).

Fire Hazards in Presence of Various Substances:

Flammable in presence of open flames and sparks. Slightly flammable to flammable in presence of oxidizing materials.

Explosion Hazards in Presence of Various Substances:

Risks of explosion of the product in presence of mechanical impact: Not available.

Risks of explosion of the product in presence of static discharge: Not available. Slightly explosive to explosive in presence of oxidizing materials.

Section 5: Fire and Explosion Data (Continued)

Fire Fighting Media and Instructions:

Flammable liquid, soluble or dispersed in water. **SMALL FIRE:** Use DRY chemical powder. **LARGE FIRE:** Use alcohol foam, water spray or fog.

Special Remarks on Fire Hazards: Not available.

Special Remarks on Explosion Hazards: Not available.

Section 6: Accidental Release Measures

Small Spill: Absorb with an inert material and put the spilled material in an appropriate waste disposal.

Large Spill:

Flammable liquid. Corrosive liquid. Keep away from heat. Keep away from sources of ignition. Stop leak if without risk. Absorb with DRY earth, sand or other non-combustible material. Do not get water inside container. Do not touch spilled material. Use water spray curtain to divert vapor drift. Prevent entry into sewers, basements or confined areas; dike if needed. Eliminate all ignition sources. Call for assistance on disposal. Be careful that the product is not present at a concentration level above TLV. Check TLV on the MSDS and with local authorities.

Section 7: Handling and Storage

Precautions:

Keep locked up Keep container dry. Keep away from heat. Keep away from sources of ignition. Ground all equipment containing material. Do not ingest. Do not breathe gas/fumes/ vapour/spray. Never add water to this product In case of insufficient ventilation, wear suitable respiratory equipment if ingested, seek medical advice immediately and show the container or the label. Avoid contact with skin and eyes.

Storage:

Flammable materials should be stored in a separate safety storage cabinet or room. Keep away from heat. Keep away from sources of ignition. Keep container tightly closed. Keep in a cool, well-ventilated place. Ground all equipment containing material. A refrigerated room would be preferable for materials with a flash point lower than 37.8°C (100°F).

Section 8: Exposure Controls/Personal Protection

Engineering Controls:

Provide exhaust ventilation or other engineering controls to keep the airborne concentrations of vapors below their respective threshold limit value. Ensure that eyewash stations and safety showers are proximal to the work-station location.

Personal Protection:

Splash goggles. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Gloves.

Personal Protection in Case of a Large Spill:

Splash goggles. Full suit. Vapor respirator. Boots. Gloves. A self contained breathing apparatus should be used to avoid inhalation of the product. Suggested protective clothing might not be sufficient; consult a specialist BEFORE handling this product.

Exposure Limits:

TWA: 10 CEIL: 75 (ppm) from ACGIH (TLV) TWA: 40 CEIL: 300 (mg/m³) from ACGIH Consult local authorities for acceptable exposure limits.

Section 9: Physical and Chemical Properties

Physical state and appearance: Liquid.

Odor : Not available.

Taste : Not available.

Molecular Weight : 98.96 g/mole

Color : Not available.

pH (1% soln/water) : Not available.

Boiling Point : 83.5°C (182.3°F)

Melting Point : -35.3°C (-31.5°F)

Critical Temperature : Not applicable.

Specific Gravity : 1.2351 (Water = 1)

Vapor Pressure : 61 mm of Hg (@ 20°C)

Vapor Density : 3.42 (Air = 1)

Volatility : Not available.

Odor Threshold : 26 ppm

Section 9: Physical and Chemical Properties (Continued)

Water/Oil Dist. Coeff.	: The product is equally soluble in oil and water; $\log(\text{oil/water}) = 0$
Ionicity (in Water)	: Not available.
Dispersion Properties	: See solubility in water, methanol, diethyl ether, n-octanol, and acetone.
Solubility	: Easily soluble in methanol, diethyl ether, n-octanol, and acetone. Very slightly Soluble in cold water.

Section 10: Stability and Reactivity Data

Stability: The product is stable.

Instability Temperature: Not available.

Conditions of Instability: Not available.

Incompatibility with various substances: Not available.

Corrosivity: Non-corrosive in presence of glass.

Special Remarks on Reactivity: Not available.

Special Remarks on Corrosivity: Not available.

Polymerization: No.

Section 11: Toxicological Information

Routes of Entry: Eye contact. Inhalation. Ingestion.

Toxicity to Animals:

WARNING: THE LC50 VALUES HEREUNDER ARE ESTIMATED ON THE BASIS OF A 4-HOUR EXPOSURE. Acute oral toxicity (LD50): 413 mg/kg [Mouse]. Acute dermal toxicity (LD50): 2800 mg/kg [Rabbit]. Acute toxicity of the vapor (LC50): 1414.2 ppm 4 hour(s) [Rat].

Section 11: Toxicological Information (Continued)

Chronic Effects on Humans:

CARCINOGENIC EFFECTS: Classified + (PROVEN) by OSHA. Classified 2B (Possible for human.) by IARC. Classified 2 (Reasonably anticipated.) by NTP. The substance is toxic to lungs, the nervous system, liver, mucous membranes.

Other Toxic Effects on Humans:

Extremely hazardous in case of ingestion. Very hazardous in case of inhalation. Hazardous in case of skin contact (irritant).

Special Remarks on Toxicity to Animals: Not available.

Special Remarks on Chronic Effects on Humans:

Passes through the placental barrier in animal. Excreted in maternal milk in human.

Special Remarks on other Toxic Effects on Humans: Not available.

Section 12: Ecological Information

Ecotoxicity: Not available.

BOD5 and COD: Not available.

Products of Biodegradation:

Possibly hazardous short term degradation products are not likely. However, long term degradation products may arise.

Toxicity of the Products of Biodegradation: The products of degradation are more toxic.

Special Remarks on the Products of Biodegradation: Not available.

Section 13: Disposal Considerations

Waste Disposal:

Section 14: Transport Information

Land transport (ADR-RID)

Proper shipping name: ETHYLENE DICHLORIDE

UN N°: 1184

H.I. nr: 336

ADR - Class: 3

Labelling - Transport: 3 : Flammable liquid. 6.1 : Toxic substances.

ADR - Group: II

Sea transport (IMDG) [English only]

Proper shipping name: ETHYLENE DICHLORIDE

UN N°: 1184

IMO-IMDG - Class or division: 3 : Flammable liquid. (6.1 : Toxic substances.)

IMO-IMDG - Packing group: II

Air transport (ICAO-IATA) [English only]

Proper shipping name: ETHYLENE DICHLORIDE

UN N°: 1184

IATA - Class or division: 3 : Flammable liquid. (6.1 : Toxic substances.)

IATA - Packing group: II

Section 15: Other Regulatory Information

Federal and State Regulations:

California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer, birth defects or other reproductive harm, which would require a warning under the statute: 1,2-Dichloroethane
California prop. 65: This product contains the following ingredients for which the State of California has found to cause cancer which would require a warning under the statute: 1,2-Dichloroethane
Pennsylvania RTK: 1,2-Dichloroethane
Massachusetts RTK: 1,2-Dichloroethane
TSCA 8(b) inventory: 1,2-Dichloroethane
CERCLA: Hazardous substances.: 1,2-Dichloroethane,

Section 15: Other Regulatory Information (Continued)

Other Regulations:

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Other Classifications:

WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-1A: Material causing immediate and serious toxic effects (VERY TOXIC). CLASS D-2A: Material causing other toxic effects (VERY TOXIC). CLASS E: Corrosive liquid.

DSCL (EEC): R11- Highly flammable. R20/22- Harmful by inhalation and if swallowed. R38- Irritating to skin. R41- Risk of serious damage to eyes. R45- May cause cancer.

HMIS (U.S.A.):

Health Hazard: 2

Fire Hazard: 3

Reactivity: 0

Personal Protection: h

National Fire Protection Association (U.S.A.):

Health: 2

Flammability: 3

Reactivity: 0

Specific hazard:

Protective Equipment:

Gloves. Lab coat. Vapor respirator. Be sure to use an approved/certified respirator or equivalent. Wear appropriate respirator when ventilation is inadequate. Splash goggles.

Section 16 - Additional Information

References: Not available.

Other Special Considerations: Not available.

OXFORD LAB FINE CHEM LLP

ISO 9001-2008 Certified Company

Regd Office: Unit no 12, 1st Floor,
Neminath Industrial Estate No.6,
Navghar, Vasai (East), Palghar - 410210.
Maharashtra, INDIA.

Tel: +91 250 2390032 / 2390989 / 2390990
Email: sales@oxfordlabchem.com /
info@oxfordlabchem.com
Web: www.oxfordlabchem.com

Oxford
Range of
Laboratory Chemicals

Disclaimer:

The information contained herein in good faith but makes no representations as to its comprehensiveness or accuracy. This document is intended only as a guide to the appropriate precautionary handling of the material by a properly trained person using this product. Individuals receiving the information must exercise their independent judgment in determining its appropriateness for a particular purpose.

Oxford Lab Fine Chem LLP makes no representations or warranties, either express or implied, including without limitation any warranties of merchantability, fitness for a particular purpose with respect to the information set forth herein or the product to which the information refers. Accordingly, Oxford Lab Fine Chem LLP will not be responsible for damages resulting from use of or reliance upon this information.